


SPECIFICATIONS (规范)>>>




Current Rating (额定电流): 0.75Amps
 Withstanding Voltage (耐电压): AC 500Vmin/Minute
 Insulation Resistance (绝缘电阻): 1000MΩ Min
 Contact Resistance (接触电阻): 20 mΩ MAX
 Operation Temperature (工作温度): -40°C to +105°C
 Material (材料)>>>
 Plastic material (塑胶材质): PA6T/PA9T/LCP+30%GF
 Color (塑胶颜色): Black
 Insulator Material (绝缘材料): Polyester (UL94V-0)
 Contact Material (接触材料): Brass
 Contact Plating (接触电镀): Au Os Sn over 40u" Ni

Dimension antitheses list(尺寸对照表)

项目	L	H	PA	PC	SQ	W
常规尺寸	6.18	1.38	2.8	2.0	0.3	3.0
客户需要						



电话(tel)	0755-23317175		 深圳市熙宸电子科技有限公司 Shenzhen xichen Electronics Technology Co.,Ltd		
传真(fax)	0755-23010246				
单位(units)	MM	设计(draw)	王刚	图名(name)	PH0.8x1.2mm 双排180度
比例(scale)	1:1	审核(ch'k)	陈晓俊	料号(Part number)	
版次(rev.)	A/1	核准(app'd)	李新亮	视图(File Name)	
视图(view)		日期(date)			



RECOMMEND P. C. B BOARD LAYOUT
 PCB TOLERANCE: ±0.05 (TOP VIEW)