





RECOMMEND P. C. B BOARD LAYOUT
PCB TOLERANCE: ± 0.05 (TOP VIEW)



SPECIFICATIONS (规范)>>>
Current Rating (额定电流): 1.0Amps
Withstanding Voltage (耐电压): AC 500Vmin/Minute
Insulation Resistance (绝缘电阻): 1000M Ω Min
Contact Resistance (接触电阻): 20 m Ω MAX
Operation Temperature (工作温度): -40 $^{\circ}$ C to +105 $^{\circ}$ C
Material (材料)>>>
Plastic material (塑胶材质): PA6T/PA9T/LCP+30%GF
Color (塑胶颜色): Black
Insulator Material (绝缘材料): Polyester (UL94V-0)
Contact Material (接触材料): Brass
Contact Plating (接触电镀): Au 0s Sn over 40u" Ni

Dimension antitheses list(尺寸对照表)							
项 目	H	PC	W				
常规尺寸	3.4	1.5 2.4	2.2				
客户需要							



电话(tel)	0755-23317175		 深圳市熙宸电子科技有限公司 Shenzhen xichen Electronics Technology Co.,Ltd			
传真(fax)	0755-23010246					
单位(units)	MM	设计(draw)	王 刚	图名(name)	PF1.27 单排180度 H3.4 防漏锡	
比例(scale)	1 : 1	审核(ch'k)	陈晓俊			
版次(rev.)	A / 1	核准(app'd)	李新亮	料号(Part number)		
视图(view)		日期(date)		图档(File Name)		